

Hydraulic Milling Machine 臥式銑槽機

機械規格 Item No.	GA-10
適用尺寸 Size (mm)	6", 8", 10", 12" Groove Joint Plier
切削行程 Stroke(mm)	50mm
前進速度 Forward Speed	100 mm/sec
後退速度 Backward Speed	100 mm/sec
伺服馬達 Servo Motor(HP)	1 HP
馬達 Motor(HP)	3 HP
工作方向 Operation Type	Horizontal/水平式
工作模式 Operation Mode	Auto/Mauul 自動/手動
工作油容量 Working Oil Capacity	150
重量 Weight(kg)	3750kg
外型規格 Dimension(mm)	2000x2900x2500mm



特點:

- 1.此機種適合工具、五金、汽車零件生產之各種槽孔。
- 2.速度快，定位高，設定容易。
- 3.定位準確，精度高，可設定達到0.01mm之精度。
- 4.使用人機介面控制，操作簡易。
- 5.一般作業員及可自行設定，無須學習程式設定。

Features:

- 1.Suitable for manufacture groove and hole of various industry.
Ex: tool, hardware, automobile components.
- 2.High speed, precise positioning, setting easy.
- 3.High correct setting & processing precision, high precision performance which can reach to 0.01mm.
- 4.Human-Computer Interaction control, easy operation.
- 5.Operator can set by their selves, no need to learn programming.

Cold Forge Shaping Machine 冷鍛成型機 Stamping Machine 壓字機 Leveling Machine 整平機

機械規格 Item No.	MT-200	MT-300	MT-420	MT-600	MT-800	MT-1000	MT-1500
機台出力 Capability (ton)	200	300	400	600	800	1000	1500
行程 Stroke(mm)	200 mm	150 mm	170 mm	200 mm	200 mm	200 mm	200 mm
上升速度 Oil cylinder rising speed (mm/sec)	150 mm/s	157 mm/s	138 mm/s	157 mm/s	158 mm/s	158 mm/s	158 mm/s
下降速度 Oil cylinder descending speed (mm/sec)	165 mm/s	170 mm/s	180 mm/s	185 mm/s	192 mm/s	200 mm/s	192 mm/s
操作壓力 Operating pressure (kg/cm²)	210 kg/cm²	210 kg/cm²	210 kg/cm²	210 kg/cm²	210 kg/cm²	210 kg/cm²	210 kg/cm²
電壓 Voltage	AC220/380	AC220/380	AC220/380	AC220/380	AC220/380	AC220/380	AC220/380
馬達 Motor (HP)	15/20 HP	20 HP	25 HP	25/30 HP	30/40 HP	40/50 HP	40/50 HP
工作方向 Operating Type	直立式/Vertical						
工作模式 Operating Method	Auto/Mauul自動/手動						
工作油容量 Working Oil capacity	450	500	650	800	1000	1200	1200
重量 Body weight (kg)	4000kg	5500kg	8500kg	9500kg	17000kg	18500kg	18500kg
外型規格 Size (mm)	1250x1300x1850	1400x1500x3000	1720x1800x3300	1900x1900x3400	2050x2230x3950	2350x2340x4200	2350x2340x4600

功能:

- 1.具快速下降、慢速成形，加工精度高。
- 2.快速、慢速可任意調整。
- 3.手動、自動，換模容易，壓力感應設定精準。
- 4.剛性結構，強力滑座設計，加工精度高，壽命長。
- 5.機械亦可依使用者工作條件量身訂做。

Function:

1. Quick down function, low speed shaping, and high processing precision.
2. Low/quick speed can be adjusted freely.
3. Manual, auto, easy to change mold, accurate setting for pressure sensor.
4. Stiffness structure, powerful slide seat design, high processing precision, and long service life.
5. Machine specification also can be designed by optional requirement of the user.



Hydraulic Milling Machine 立式單軸銑槽機

機械規格 Item No.	GB-10-S (單軸)
適用尺寸 Size (mm)	Gear Wrench
切削行程 Stroke(mm)	50mm
上升速度 Up Speed(mm/s)	135 mm/sec
下降速度 Down Speed(mm/s)	135 mm/sec
伺服馬達 Servo Motor(HP)	1/1.5 HP
馬達 Motor(HP)	2 HPx2
工作方向 Operation Type	Vertical/直立式
工作模式 Operation Mode	Auto/Mauul 自動/手動
工作油容量 Working Oil Capacity	100
重量 Weight(kg)	1800kg
外型規格 Dimension(mm)	1300x1400x2020mm



特點:

- 1.此機種適合工具、五金、汽車零件生產之各種槽孔。
- 2.速度快，定位高，設定容易。
- 3.定位準確，精度高，可設定達到0.01mm之精度。
- 4.使用人機介面控制，操作簡易。
- 5.一般作業員及可自行設定，無須學習程式設定。

Features:

- 1.Suitable for manufacture groove and hole of various industry.
Ex: tool, hardware, automobile components.
- 2.High speed, precise positioning, setting easy.
- 3.High correct setting & processing precision, high precision performance which can reach to 0.01mm.
- 4.Human-Computer Interaction control, easy operation.
- 5.Operator can set by their selves, no need to learn programming.

Hydraulic Milling Machine 立式雙軸銑槽機

機械規格 Item No.	GB-10-2 (雙軸)
適用尺寸 Size (mm)	Gear Wrench
切削行程 Stroke(mm)	50mm
上升速度 Up Speed(mm/s)	135 mm/sec
下降速度 Down Speed(mm/s)	130 mm/sec
伺服馬達 Servo Motor(HP)	1/1.5 HP
馬達 Motor(HP)	2 HPx2
工作方向 Operation Type	Vertical/直立式
工作模式 Operation Mode	Auto/Mauul 自動/手動
工作油容量 Working Oil Capacity	200
重量 Weight(kg)	3100kg
外型規格 Dimension(mm)	2030x1700x2120mm



特點:

- 1.此機種適合工具、五金、汽車零件生產之各種槽孔。
- 2.速度快，定位高，設定容易。
- 3.定位準確，精度高，可設定達到0.01mm之精度。
- 4.使用人機介面控制，操作簡易。
- 5.一般作業員及可自行設定，無須學習程式設定。

Features:

- 1.Suitable for manufacture groove and hole of various industry.
Ex: tool, hardware, automobile components.
- 2.High speed, precise positioning, setting easy.
- 3.High correct setting & processing precision, high precision performance which can reach to 0.01mm.
- 4.Human-Computer Interaction control, easy operation.
- 5.Operator can set by their selves, no need to learn programming.